



NO NOTE UNLESS OTHERWISE SPECIFIED

Hole for panelmounting of DP200

Fastening hole. Depth 11 mm. May be threaded M3 and used with std screw.

DP200 Panel bracket 10105917

Chamfer edges 0,2-0,5 mm

R11,6±0,5 (4x)

R500,2(4x)

R5,2(4x)

Sealing surface area crosshatched
 0,2 Surface max Ra0.8
 Panel thickness 2-5 mm

Screw M3x10 self tapping
 Wn 5451 30x10-S Delta PT
 10107464 (1x)
 Torque Mv=0.9 Nm

Reassembly with self tapping screw may damage existing thread in housing!

Tolerance according to SS-ISO 2768-m

DP200 Panel seal red 10107630 or
 DP200 Panel seal black 10107631

ONLY ONE IN USE

DOC NO				DATE	NAME	MATERIAL / SPECIFICATION		
				DRAFTER	07-FEB-07	M.Loennberg		
				DESIGNER				
B		070918	D Nilsson	ENGINEER			RAW PART NO	
							SIZE	
REV	AUTH	DATE	NAME				TITLE	
						DP200 Installation drawing		
						SCALE	1:1	DWG NO
				SHEET		1 OF 1	10105920	B

THE REPRODUCTION, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS THE COMMUNICATION OF ITS CONTENTS TO OTHERS WITHOUT EXPLICIT AUTHORIZATION IS PROHIBITED. OFFENDERS WILL BE HELD LIABLE FOR THE PAYMENT OF DAMAGES. ALL RIGHTS RESERVED IN THE EVENT OF THE GRANT OF A PATENT, UTILITY MODEL OR DESIGN. (PER ISO 16016)